


# EZQ 20/2 B



## Short description

Axial wall fan with square wall plate, DN 200, single-phase AC

## Application examples

Production facility, Commercial premises, Garage, Building container, Storage facility

Article number 0083.0102

## Technical data

Model	Square wall plate
Air flow volume	1.100 m <sup>3</sup> /h
Rotating speed	2.850 1/min
Impeller type	axial
Speed controllable	✓
Reversing capacity	✓
Type of voltage	Alternating current
Rated voltage	230 V
Frequency	50 Hz
Nominal output	65 W
I <sub>nom</sub>	0,3 A
I <sub>max</sub>	0,47 A
Degree of protection	IP 55
Insulation class	B
Pole-changeable	–
Installation site	Wall / Ceiling
Type of installation	Surface-mounted
Installation position	horizontal / vertical
Material	Sheet steel, galvanised
Colour	Silver
Weight	5,5 kg
Weight including packaging	6,44 kg
Nominal size	200 mm
Width	345 mm
Height	345 mm
Depth	238 mm
Width with packaging	415 mm
Height with packaging	415 mm
Depth with packaging	295 mm

# EZQ 20/2 B

Airstream temperature at nominal current	60 °C
Airstream temperature at I <sub>Max</sub>	-20 °C up to 60 °C
Packing unit	1 piece
Range	C
GTIN (EAN)	4012799831020

## Sound power level in octave range


	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
<b>L<sub>WA7, S1</sub></b> <b>(dB(A))</b>	17	28	33	33	38	34	28	23	42
<b>L<sub>WA7, S2</sub></b> <b>(dB(A))</b>	28	39	54	55	58	59	58	48	64
<b>L<sub>WA7, S3</sub></b> <b>(dB(A))</b>	33	43	60	62	64	65	64	56	70
<b>L<sub>WA7, S4</sub></b> <b>(dB(A))</b>	34	44	55	67	67	66	66	58	73
<b>L<sub>WA7, S5</sub></b> <b>(dB(A))</b>	34	44	53	68	68	67	67	59	74
<b>L<sub>WA8, S1</sub></b> <b>(dB(A))</b>	18	32	35	36	42	37	31	25	45
<b>L<sub>WA8, S2</sub></b> <b>(dB(A))</b>	32	40	55	54	62	62	63	60	68
<b>L<sub>WA8, S3</sub></b> <b>(dB(A))</b>	42	47	61	61	67	68	69	66	74
<b>L<sub>WA8, S4</sub></b> <b>(dB(A))</b>	45	50	57	68	70	70	71	68	76
<b>L<sub>WA8, S5</sub></b> <b>(dB(A))</b>	47	51	57	69	71	71	72	69	77

L<sub>WA7</sub>= housing and free inlet sound power level in dB.

L<sub>WA8</sub>= housing and free outlet sound power level in dB.


# EZQ 20/2 B

## Characteristic curve



## Dimensioned drawing [mm]

- ① Steel wall plate = EZQ/DZQ model
- ② Steel wall ring = EZS/DZS model



# EZQ 20/2 B

Dimensioned drawing [mm]

